



(Sheet A) Cable Performance specification

| | | MMF(50 μ m 10G) |
|-------------|----------|-------------------|
| Band width | 0.85 μ m | Over 1500(MHz Km) |
| | 1.3 μ m | Over 500(MHz Km) |
| ATTENUATION | 0.85 μ m | Under 3.0(dB/Km) |
| | 1.3 μ m | Under 1.0(dB/Km) |

| manufacture/description/quantity | | | |
|----------------------------------|-------------------------------------|------------------|----|
| ① | DLC MM Connector with CLIP | Clip color=clear | 6 |
| ② | BOOT | | 12 |
| ③ | 10G(OM3) 12C RIBBON CABLE | COLOR=AQUA | |
| ④ | 10G(OM3) 50/125 φ2.0mm SIMPLEX CORD | COLOR=AQUA | 12 |
| ⑤ | FAN-OUT | | 1 |
| ⑥ | MPO MM Connector | COLOR=AQUA | 1 |
| ⑦ | Number Label | | 12 |
| ⑧ | Serial number label | | 1 |

*All of units are Millimeter
 *The optical specification is satisfying the sheet A.
 *Ferrule:MPO=FLAT,DLC=PC
 *Without the PIN of MPO connector

DRAWING#



CONNECTING WORK
 人と未来と情報、信頼のインターフェース
 エイム電子株式会社

承認

作図

ROHS COMPLIANT